

Technical - Specification Guides

To ensure you are supplied genuine **Polynum™** as specified, always document as follows:

Product Name: **Polynum™ Double Bubbles**

The insulation material shall be **Polynum™ Double Bubbles** fibre-free, thermo-cellular reflective insulation 8.0mm thick, consists of two layers of 4.00mm bubbles each, and two reflective layers, with low Emissivity (0.03 to 0.05 for each reflective surface), manufactured by Polyon Industries.

2. The insulation material shall comply with AS/NZS 4859.1 and, and be tested and certified to the following:
 - AS/NZS 4859.1
 - AS/NZS 4859.1 Appendix 1
 - ASTM-E408
 - ASTM-C1371: 1998
 - AS 1530.3
 - ASTM-E96
 - ASTM C – 1338
 - ASTM C 1136-92
 - ASTM E84-97a
 - BS476 Part 7
 - ASTM 384-90
3. The insulation material shall be installed as recommended at **Polynum™** Insulation's Installation Instructions and guides.
4. Submittals:
 - Product Data: Manufacturer's descriptive literature for reflective insulation material; indicate compliance to specified product characteristics, including documentation of code compliance, if documentation is required.
 - Verification Samples: Two samples, minimum size 8 inches (203 mm) square, of actual products to be installed.
 - Quality Assurance Submittals: Manufacturer's printed installation instructions for each indicated project condition; include recommended fastening materials and techniques.

5. Delivery Storage and Handling:

Store products of this section in manufacturer's unopened packaging until installation; maintain storage conditions recommended by manufacturer. Store in clean, dry area. Do not expose to rain, dew, or snow while still in roll form.

End of Specifications

polynum